

## General Description

SFGMOS<sup>®</sup>

low

$R_{DS(ON)}$ , low gate charge, fast switching and excellent avalanche characteristics. The low  $V_{th}$  series is specially designed to use in synchronous rectification power systems with low driving voltage.

## Features

- Low  $R_{DS(ON)}$  & FOM
- Extremely low switching loss
- Excellent reliability and uniformity
- Fast switching and soft recovery



## Applications

- PD charger
- Motor driver
- Switching voltage regulator
- DC-DC convertor
- Switched mode power supply

## Key Performance Parameters

| Parameter                     | Value | Unit |
|-------------------------------|-------|------|
| $V_{DS, min} @ T_{j(max)}$    | 100   | V    |
| $I_D, pulse$                  | 64    | A    |
| $R_{DS(ON) max} @ V_{GS}=10V$ | 8     |      |
| $Q_g$                         | 60.7  | nC   |

## Marking Information

| Product Name | Package | Marking   |
|--------------|---------|-----------|
| SFG10R08BF   | SOP8    | SFG10R08B |

## Package & Pin information



**Absolute Maximum Ratings** at  $T_j=25^\circ\text{C}$  unless otherwise noted

| Parameter   | Symbol               | Value      | Unit             |
|---|----------------------|------------|------------------|
| Drain source voltage  | $V_{DS}$             | 100        | V                |
| Gate source voltage   | $V_{GS}$             | $\pm 20$   | V                |
| Continuous drain current <sup>1)</sup> , $T_C=25^\circ\text{C}$         | $I_D$                | 16         | A                |
| Pulsed drain current <sup>2)</sup> , $T_C=25^\circ\text{C}$             | $I_{D,\text{pulse}}$ | 64         | A                |
| Continuous diode forward current <sup>1)</sup> , $T_C=25^\circ\text{C}$ | $I_S$                | 16         | A                |
| Diode pulsed current <sup>2)</sup> , $T_C=25^\circ\text{C}$             | $I_{S,\text{Pulse}}$ | 64         | A                |
| Power dissipation <sup>3)</sup> , $T_C=25^\circ\text{C}$                | $P_D$                | 4          | W                |
| Single pulsed avalanche energy <sup>5)</sup>                            | $E_{AS}$             | 130        | mJ               |
| Operation and storage temperature                                       | $T_{stg}, T_j$       | -55 to 150 | $^\circ\text{C}$ |

**Thermal Characteristics**

| Parameter  | Symbol | Value | Unit               |
|--|--------|-------|--------------------|
| Thermal resistance, junction-ambient <sup>4)</sup> | R      | 31    | $^\circ\text{C/W}$ |


**Electrical Characteristics** at  $T_j=25^\circ\text{C}$  unless otherwise specified

| Parameter                        | Symbol              | Min. | Typ. | Max. | Unit | Test condition                             |
|----------------------------------|---------------------|------|------|------|------|--|
| Drain-source breakdown voltage   | $BV_{DSS}$          | 100  |      |      | V    | $V_{GS}=0 \text{ V}$ , $I_D=250 \text{ A}$ |
| Gate threshold voltage           | $V_{GS(\text{th})}$ | 1.0  |      | 2.5  | V    | $V_{DS}=V_{GS}$ , $I_D=250 \text{ A}$      |
| Drain-source on-state resistance | $R_{DS(\text{ON})}$ |      | 6.5  | 8.0  |      | $V_{GS}=10 \text{ V}$ , $I_D=12 \text{ A}$ |
| Drain-source on-state resistance | $R_{DS(\text{ON})}$ |      | 8.5  | 10.0 |      | $V_{GS}=4.5 \text{ V}$ , $I_D=9 \text{ A}$ |
| Gate-source leakage current      | $I_{GSS}$           |      |      | 100  | nA   | $V_{GS}=20 \text{ V}$                      |
|                                  |                     |      |      | -100 |      | $V_{GS}=-20 \text{ V}$                     |
| Drain-source leakage current     |                     |      |      |      |      |  |


**Dynamic Characteristics**

| Parameter                    | Symbol       | Min. | Typ. | Max. | Unit | Test condition   |
|------------------------------|--------------|------|------|------|------|--|
| Input capacitance            | $C_{iss}$    |      | 3530 |      | pF   | $V_{GS}=0\text{ V},$<br>$V_{DS}=50\text{ V},$<br>MHz                         |
| Output capacitance           | $C_{oss}$    |      | 560  |      | pF   |  |
| Reverse transfer capacitance | $C_{rss}$    |      | 9.0  |      | pF   |  |
| Turn-on delay time           | $t_{d(on)}$  |      | 22.5 |      | ns   | $V_{GS}=10\text{ V},$<br>$V_{DS}=50\text{ V},$<br>$R_G$<br>$I_D=10\text{ A}$ |
| Rise time                    | $t_r$        |      | 8.6  |      | ns   |  |
| Turn-off delay time          | $t_{d(off)}$ |      | 66.6 |      | ns   |  |
| Fall time                    | $t_f$        |      |      |      |      |  |


## Electrical Characteristics Diagrams




**Figure 1. Typ. output characteristics**




**Figure 2. Typ. transfer characteristics**




**Figure 3. Typ. capacitances**



**Figure 4. Typ. gate charge**



**Figure 5. Drain-source breakdown voltage**



**Figure 6. Drain-source on-state resistance**




Figure 7. Drain-source on-state resistance




Figure 8. Forward characteristic of body diode






Figure 9. Safe operation area  $T_c=25\text{ }^\circ\text{C}$


### Test circuits and waveforms




**Figure 1. Gate charge test circuit & waveform**



**Figure 2. Switching time test circuit & waveform**




**Figure 3. Unclamped inductive switching (UIS) test circuit & waveform**



**Figure 4. Diode reverse recovery test circuit & waveform**

## Package Information



| Symbol | mm       |      |      |
|--------|----------|------|------|
|        | Min      | Nom  | Max  |
| A      | 1.35     | 1.55 | 1.75 |
| A1     | 0.10     | 0.15 | 0.25 |
| A2     | 1.25     | 1.40 | 1.65 |
| A3     | 0.50     | 0.60 | 0.70 |
| b      | 0.38     | -    | 0.51 |
| L1     | 1.04 REF |      |      |
| L2     | 0.25 BSC |      |      |
| b1     | 0.37     | 0.42 | 0.47 |
| c      | 0.18     | -    | 0.25 |
| c1     | 0.17     | 0.20 | 0.23 |
| D      | 4.80     | 4.90 | 5    |
| E      | 5.80     | 6.00 | 6.20 |
| E1     | 3.80     | 3.90 | 4.00 |
| e      | 1.17     | 1.27 | 1.37 |
| L      | 0.45     | 0.60 | 0.80 |
| R      | 0.07     | -    | -    |
| R1     | 0.07     | -    | -    |
| h      | 0.30     | 0.40 | 0.50 |
|        | 0        | -    |      |
|        |          |      |      |
|        |          |      |      |
|        |          |      |      |
|        |          |      |      |

Version 1: SOP8-K package outline dimension

## Ordering Information

| Package Type | Units/Reel | Reels / Inner Box | Units/Inner Box | Inner Boxes/Carton Box | Units/Carton Box |
|--------------|------------|-------------------|-----------------|------------------------|------------------|
| SOP8         |            |                   |                 |                        |                  |