

# TMP3N90/TMPF3N90

## TMP3N90G/TMPF3N90G


### Features

- Low gate charge
- 100% avalanche tested
- Improved dv/dt capability
- RoHS compliant
- Halogen free package
- JEDEC Qualification

$$V_{DSS} = 990 \text{ V @ } T_{jmax}$$

$$I_D = 2.5 \text{ A}$$

$$R_{DS(ON)} = 5.1 \Omega(\text{max}) @ V_{GS} = 10 \text{ V}$$



### Absolute Maximum Ratings

Parameter	Symbol	TMP3N90(G)	TMPF3N90(G)	Unit
Drain-Source Voltage	$V_{DSS}$	900		V
Gate-Source Voltage	$V_{GS}$	±30		V
Continuous Drain Current	$T_C = 25 \text{ }^\circ\text{C}$	2.5	2.5 *	A
	$T_C = 100 \text{ }^\circ\text{C}$	1.6	1.6 *	A
Pulsed Drain Current (Note 1)	$I_{DM}$	10	10*	A
Single Pulse Avalanche Energy (Note 2)	$E_{AS}$	16.6		mJ
Repetitive Avalanche Current (Note 1)	$I_{AR}$	2.5		A
Repetitive Avalanche Energy (Note 1)	$E_{AR}$	9.4		mJ
Power Dissipation	$T_C = 25 \text{ }^\circ\text{C}$	94	32	W
	Derate above 25 °C	0.75	0.25	W/°C
Peak Diode Recovery dv/dt (Note 3)	dv/dt	4.5		V/ns
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55~150		°C
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	$T_L$	300		°C

### Thermal Characteristics

Parameter	Symbol	TMP3N90(G)	TMPF3N90(G)	Unit
Maximum Thermal resistance, Junction-to-Case	$R_{\theta JC}$	1.33	3.9	°C/W
Maximum Thermal resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	62.5	°C/W

### Electrical Characteristics : $T_C=25^\circ\text{C}$ , unless otherwise noted

Parameter	Symbol	Test condition	Min	Typ	Max	Units
<b>OFF</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$	900	--	--	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 900\text{ V}, V_{GS} = 0\text{ V}$	--	--	10	$\mu\text{A}$
		$V_{DS} = 720\text{ V}, T_C = 125^\circ\text{C}$	--	--	100	$\mu\text{A}$
Forward Gate-Source Leakage Current	$I_{GSSF}$	$V_{GS} = 30\text{ V}, V_{DS} = 0\text{ V}$	--	--	100	nA
Reverse Gate-Source Leakage Current	$I_{GSSR}$	$V_{GS} = -30\text{ V}, V_{DS} = 0\text{ V}$	--	--	-100	nA

### ON

Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	2	--	4	V
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = 10\text{ V}, I_D = 1.25\text{ A}$	--	4.3	5.1	$\Omega$
Forward Transconductance (Note 4)	$g_{FS}$	$V_{DS} = 30\text{ V}, I_D = 1.25\text{ A}$	--	3	--	S

### DYNAMIC

Input Capacitance	$C_{iss}$	$V_{DS} = 25\text{ V}, V_{GS} = 0\text{ V},$ $f = 1.0\text{ MHz}$	--	748	--	pF
Output Capacitance	$C_{oss}$		--	55	--	pF
Reverse Transfer Capacitance	$C_{rss}$		--	8.7	--	pF

### SWITCHING

Turn-On Delay Time (Note 4,5)	$t_{d(on)}$	$V_{DD} = 450\text{ V}, I_D = 2.5\text{ A},$ $R_G = 25\ \Omega$	--	16	--	ns
Turn-On Rise Time (Note 4,5)	$t_r$		--	25	--	ns
Turn-Off Delay Time (Note 4,5)	$t_{d(off)}$		--	63	--	ns
Turn-Off Fall Time (Note 4,5)	$t_f$		--	31	--	ns
Total Gate Charge (Note 4,5)	$Q_g$	$V_{DS} = 720\text{ V}, I_D = 2.5\text{ A},$ $V_{GS} = 10\text{ V}$	--	17	--	nC
Gate-Source Charge (Note 4,5)	$Q_{gs}$		--	2.4	--	nC
Gate-Drain Charge (Note 4,5)	$Q_{gd}$		--	6.6	--	nC






### SOURCE DRAIN DIODE

Maximum Continuous Drain-Source Diode Forward Current	$I_S$	---	--	--	2.5	A
Maximum Pulsed Drain-Source Diode Forward Current	$I_{SM}$	---	--	--	10	A
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS} = 0\text{ V}, I_S = 2.5\text{ A}$	--	--	1.5	V
Reverse Recovery Time (Note 4)	$t_{rr}$	$V_{GS} = 0\text{ V}, I_S = 2.5\text{ A}$ $di_F / dt = 100\text{ A}/\mu\text{s}$	--	355	--	ns
Reverse Recovery Charge (Note 4)	$Q_{rr}$		--	1.8	--	$\mu\text{C}$





Note :

1. Repeated rating : Pulse width limited by safe operating area
2.  $L = 5.0\text{ mH}, I_{AS} = 2.5\text{ A}, V_{DD} = 50\text{ V}, R_G = 25\ \Omega$ , Starting  $T_J = 25^\circ\text{C}$
3.  $I_{SD} \leq 2.5\text{ A}, di/dt \leq 200\text{ A}/\mu\text{s}, V_{DD} \leq BV_{DS}$ , Starting  $T_J = 25^\circ\text{C}$
4. Pulse Test : Pulse width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$
5. Essentially Independent of Operating Temperature Typical Characteristics

# TMP3N90/TMPF3N90 TMP3N90G/TMPF3N90G





# TMP3N90/TMPF3N90 TMP3N90G/TMPF3N90G




## TMP3N90(G)

## TMPF3N90(G)







TMP3N90(G)



TMPF3N90(G)




TO-220AB-3L MECHANICAL DATA



SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	0.170	0.180	4.32	4.57	
b	0.028	0.036	0.71	0.91	
b <sub>1</sub>	0.045	0.055	1.15	1.39	
c	0.014	0.021	0.36	0.53	
D	0.590	0.610	14.99	15.49	
E	0.530	0.550	13.47	13.97	
e	0.100 TYP.		2.54 TYP.		
e <sub>1</sub>	0.200 BSC		5.08 BSC		
F	0.048	0.054	1.22	1.37	
H <sub>1</sub>	0.235	0.255	5.97	6.47	
J <sub>1</sub>	0.100	0.110	2.54	2.79	
L	0.530	0.550	13.47	13.97	
L <sub>1</sub>	0.130	0.150	3.31	3.81	
∅P	0.149	0.157	3.78	3.98	
Q	0.102	0.112	2.60	2.84	

TO-220F-3L MECHANICAL DATA



NC M	JODI F !		NJMJNF F !!		O F !
	NJO!	NB !	NJO!	NB !	
B!	1 289!!	1 2 5!!	5 64!!	5 4!!	!
!	1 139!!	1 147!!	1 82!!	1 2!!	!
D!	1 129!	1 135!	1 56!	1 71!	!
E!	1 728!!	1 744!!	26 78!!	27 18!!	!
F!	1 4 3!!	1 519!!	7!!	21 47!!	!
!	1 211!	!	3 65	!	!
I 2!	1 367!!	1 383!!	7 61!!	7 1!!	!
2!	1 212!!	1 228!!	3 67!!	3 7!!	!
M	1 614!!	1 62 !!	23 89!!	24 29!!	!
φQ!	1 228!!	1 244!!	3 9!!	4 49!!	!
2!	1 156!!	1 166!!	2 26!!	2 4 !!	!
M2!	1 225!	1 241!!	3 !!	4 4!!	!
2!	1 233!!	1 249!!	4 21!!	4 61!!	!
!	1 1 3!	1 219!	3 45!	3 85!	