




## Features

- Max Junction Temperature 150°C
- High breakdown voltage up to 650V for improved reliability
- Short Circuit Rated
- Very Low Saturation Voltage:  
 $V_{CE(SAT)} = 1.65V$  (Typ.) @  $I_C = 15A$
- Soft current turn-off waveforms

<b><math>V_{CE}</math></b>	<b>650</b>	<b>V</b>
<b><math>I_C</math></b>	<b>15</b>	<b>A</b>
<b><math>V_{CE(SAT)}</math> <math>I_C=15A</math></b>	<b>1.65</b>	<b>V</b>

## Applications

- Soft switching applications
- Air conditioning
- Motor drive inverter



Product	Package	Packaging
YGP15N65T1	TO-220	Tube
YGK15N65T1	TO-263	Tube
YGF15N65T1	TO-220F	Tube

**Maximum Ratings**     $T_j = 25^\circ\text{C}$  unless otherwise specified

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	$V_{CE}$	650	V
DC collector current, limited by $T_{j\max}$ $T_C = 25^\circ\text{C}$ $T_C = 100^\circ\text{C}$	$I_C$	30 15	A
Diode Forward current, limited by $T_{j\max}$ $T_C = 25^\circ\text{C}$ $T_C = 100^\circ\text{C}$	$I_F$	30 15	A
Continuous Gate-emitter voltage	$V_{GE}$	$\pm 20$	V
Transient Gate-emitter voltage	$V_{GE}$	$\pm 30$	V
Turn off safe operating area $V_{CE} = 650\text{V}$ , $T_j = 150^\circ\text{C}$	-	60	A
Pulsed collector current, $V_{GE}=15\text{V}$ , $t_p$ limited by $T_{j\max}$	$I_{CM}$	45	A

Short Circuit Withstand Time, V

---

**Electrical Characteristics of the IGBT  $T_j$**

**Switching Characteristic, Inductive Load**  $T_j = 25^\circ\text{C}$  unless otherwise specified

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
<b>Dynamic</b>						
Turn-on Delay Time	$t_{d(on)}$	$T_j = 25^\circ\text{C}$ $V_{CC} = 400\text{V}$ , $I_C = 15\text{A}$ , $V_{GE} = 0/15\text{V}$ , $R_g = 12\Omega$	-	15	-	ns
Rise Time	$t_r$		-	25	-	ns
Turn-off Delay Time	$t_{d(off)}$		-	60	-	ns
Fall Time	$t_f$		-	46	-	ns
Turn-on Energy	$E_{on}$		-	0.75	-	mJ
Turn-off Energy	$E_{off}$		-	0.1	-	mJ

**Electrical Characteristics of the DIODE**  $T_j = 25^\circ\text{C}$  unless otherwise specified

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
<b>Dynamic</b>						
Diode Forward Voltage	$V_{FM}$	$I_F = 15\text{A}$	-	1.7	-	V

 Reverse Recovery Time  $Tr_{rr}$  - 50 - ns 5I 5 I 5

 $I_F = 15\text{A}$   
 $VR = 300\text{V}$ ,  
 $di/dt = 200\text{A}/\mu\text{s}$

Fig. 1 FBSOA characteristics for TO-220F




Fig. 2 FBSOA characteristics for TO-220 and TO-263

Fig. 3 Load Current vs. Frequency for TO-220F

Fig.4 Load Current vs. Frequency TO-220 and TO-263

Fig. 5 Output characteristics




Fig. 6 Saturation voltage characteristics




Fig. 7 Switching times vs. gate resistor

Fig. 8 Switching times vs. collector current

Fig. 9 Switching loss vs. gate resistor




Fig. 10 Switching loss vs. collector current





Fig. 11 Gate charge characteristics



Fig. 12 Capacitance characteristics






### TO-220F package information






## TO-263 package information



SYMBOL	MM		
	MIN	NOM	MAX
A	4.37	4.57	4.77
A1	1.22	1.27	1.42
A2	2.49	2.69	2.89
A3	0.00	0.13	0.25
b	0.70	0.81	0.96
b1	1.17	1.27	1.47
c	0.30	0.38	0.53
D1	8.50	8.79	8.90
D4	6.60	-	-
E	9.86	10.16	10.36
E5	7.06	-	-
e	2.54 BSC		
H	14.70	15.13	15.50
H2	1.07	1.27	1.47
L	2.00	2.30	2.60
L1	1.40	1.55	1.70
L4	0.25 BSC		
θ	0°	5°	9°



## TO-220 package information



SYMBOL	MIN	NOM	MAX
A <sub>1</sub>	4.40	4.50	4.60
A <sub>2</sub>	1.27	1.30	1.33
b	2.30	2.40	2.50
b <sub>1</sub>	0.70	—	0.90
c	1.27	—	1.40
D	0.45	0.50	0.60
D <sub>1</sub>	15.30	15.70	16.10
D <sub>2</sub>	9.10	9.20	9.30
E	13.10	—	13.70
E <sub>1</sub>	9.70	9.90	10.20
e	7.80	8.00	8.20
e <sub>1</sub>	2.54BSC	—	—
H <sub>1</sub>	5.08BSC	—	—
L	6.30	6.50	6.70
L <sub>1</sub>	12.78	13.08	13.38
L <sub>2</sub>	—	—	3.50
ØP	4.60REF	3.55	3.60
Q	2.73	—	2.87
$\theta_1$	1°	3°	5°

