

Absolute Maximum Ratings at $T_j=25$ unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	650	V
Gate-source voltage	V_{GS}	± 30	V
Continuous drain current ¹⁾ , $T_C=25$ °C	I_D	8	A
Continuous drain current ¹⁾ , $T_C=100$ °C		5	
Pulsed drain current ²⁾ , $T_C=25$ °C	$I_{D, pulse}$	24	A
Continuous diode forward current ¹⁾ , $T_C=25$ °C	I_S	8	A
Diode pulsed current ²⁾ , $T_C=25$ °C	$I_{S, pulse}$	24	A
Power dissipation ³⁾ , $T_C=25$ °C	P_D	26	W
Single pulsed avalanche energy ⁵⁾	E_{AS}	125	mJ
MOSFET dv/dt ruggedness, V_{DS} 480 V	dv/dt	50	V/ns
Reverse diode dv/dt, V_{DS} 480 V, I_{SD} D	dv/dt	15	V/ns
Operation and storage temperature	T_{stg}, T_j	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal resistance, junction-case	R	4.81	°C/W
Thermal resistance, junction-ambient ⁴⁾	R	62.5	°C/W

Electrical Characteristics at $T_j=25$ unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Drain-source breakdown voltage	BV_{DSS}	650			V	$V_{GS}=0$ V, $I_D=250$ A
		700				$V_{GS}=0$ V, $I_D=250$ A, $T_j=150$ °C
Gate threshold voltage	$V_{GS(th)}$	2.9		3.9	V	$V_{DS}=V_{GS}$, $I_D=250$ A
Drain-source on-state resistance	$R_{DS(on)}$		0.5	0.58		$V_{GS}=10$ V, $I_D=4$ A
			1.4			$V_{GS}=10$ V, $I_D=4$ A, $T_j=150$ °C
Gate-source leakage current	I_{GSS}			100	nA	$V_{GS}=30$ V
				-100		$V_{GS}=-30$ V
Drain-source leakage current	I_{DSS}			1	A	$V_{DS}=650$ V, $V_{GS}=0$ V
Gate resistance	R_G		47			f= 1 MHz, Open drain

Dynamic Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Input capacitance	C_{iss}				pF	$V_{GS}=0\text{ V}$, $V_{DS}=50\text{ V}$, 00 kHz
Output capacitance	C_{oss}		41.7		pF	
Reverse transfer capacitance	C_{rss}		3.1		pF	
Turn-on delay time	$t_{d(on)}$		26.4		ns	$V_{GS}=10\text{ V}$, $V_{DS}=400\text{ V}$, $R_G=3$ $I_D=4\text{ A}$
Rise time	t_r		17.9		ns	
Turn-off delay time	$t_{d(off)}$		56.2		ns	
Fall time	t_f		14		ns	

Gate Charge Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Total gate charge	Q_g		8.6		nC	$V_{GS}=10\text{ V}$, $V_{DS}=400\text{ V}$, $I_D=4\text{ A}$
Gate-source charge	Q_{gs}		2.2		nC	
Gate-drain charge	Q_{gd}		3.8		nC	
Gate plateau voltage	$V_{plateau}$		5.7		V	

Body Diode Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Diode forward voltage	V_{SD}			1.3	V	$I_S=8\text{ A}$, $V_{GS}=0\text{ V}$
Reverse recovery time	t_{rr}		214.3		ns	$I_S=4\text{ A}$, '
Reverse recovery charge	Q_{rr}		1.7		C	
Peak reverse recovery current	I_{rrm}		16.1		A	

Note

- 1) Calculated continuous current based on maximum allowable junction temperature.
- 2) Repetitive rating; pulse width limited by max. junction temperature.
- 3) P_d is based on max. junction temperature, using junction-case thermal resistance.
- 4) The value of R_{θ} is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_a=25\text{ °C}$.
- 5) $V_{DD}=100\text{ V}$, $V_{GS}=10\text{ V}$, $L=79.9\text{ mH}$, starting $T_j=25\text{ °C}$.

Electrical Characteristics Diagrams




Figure 1. Typ. output characteristics




Figure 2. Typ. transfer characteristics




Figure 3. Typ. capacitances




Figure 4. Typ. gate charge



Figure 5. Drain-source breakdown voltage




Figure 6. Drain-source on-state resistance




Figure 7. Threshold voltage




Figure 8. Forward characteristic of body diode




Figure 9. Drain-source on-state resistance




Figure 10. Drain current




Figure 11. Safe operation area $T_c=25\text{ °C}$

Test circuits and waveforms




Figure 1. Gate charge test circuit & waveform



Figure 2. Switching time test circuit & waveforms




Figure 3. Unclamped inductive switching (UIS) test circuit & waveforms




Figure 4. Diode reverse recovery test circuit & waveforms

Enhancement Mode N-

Ordering Information

Package Type	Units/ Tube	Tubes/ Inner Box	Units/ Inner Box	Inner Boxes/ Carton Box	Units/ Carton Box
TO220F-C	50	20	1000	6	6000

Product Information

Product	Package	Pb Free	RoHS	Halogen Free
OSG65R580FTF	TO220F	yes	yes	yes