



N-channel MOSFET

## Features

- Low gate charge
- 100% avalanche tested
- Improved dv/dt capability
- RoHS compliant
- Halogen free package
- JEDEC Qualification

$BV_{DSS}$	$I_D$	$R_{DS(on)}$
600V	12A	< 0.65Ω



Device	Package	Marking	Remark
TMP12N60A / TMPF12N60A	TO-220 / TO-220F	TMP12N60A / TMPF12N60A	RoHS
TMP12N60AG / TMPF12N60AG	TO-220 / TO-220F	TMP12N60AG / TMPF12N60AG	Halogen Free

## Absolute Maximum Ratings

Parameter	Symbol	TMP12N60A(G)	TMPF12N60A(G)	Unit	
Drain-Source Voltage	$V_{DSS}$	600		V	
Gate-Source Voltage	$V_{GS}$	30		V	
Continuous Drain Current	$I_D$	$T_C = 25$	12	12 *	A
		$T_C = 100$	7.2	7.2 *	A
Pulsed Drain Current (Note 1)	$I_{DM}$	48	48 *	A	
Single Pulse Avalanche Energy (Note 2)	$E_{AS}$	825		mJ	
Repetitive Avalanche Current (Note 1)	$I_{AR}$	12		A	
Repetitive Avalanche Energy (Note 1)	$E_{AR}$	23.1		mJ	
Power Dissipation	$P_D$	$T_C = 25$	231	53.4	W
		Derate above 25	1.85	0.42	W/
Peak Diode Recovery dv/dt (Note 3)	dv/dt	4.5		V/ns	
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55~150			
Maximum lead temperature for soldering purposes,	$T_L$	300			

\* Limited only by maximum junction temperature

## Thermal Characteristics







Parameter	Symbol	TMP12N60A(G)	TMPF12N60A(G)	Unit
Maximum Thermal resistance, Junction-to-Case	$R_{\theta JC}$	0.54	2.34	/W
Maximum Thermal resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	62.5	/W









**Electrical Characteristics** :  $T_C=25$  , unless otherwise noted

Note :


1. Repeated rating : Pulse width limited by safe operating area
2.  $L=10.5\text{mH}$ ,  $I_{AS} = 12\text{A}$ ,  $V_{DD} = 50\text{V}$ ,  $R_G = 25$  , Starting  $T_J= 25$







TO-220AB-3L MECHANICAL DATA



SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	0.170	0.180	4.32	4.57	
b	0.028	0.036	0.71	0.91	
b <sub>1</sub>	0.045	0.055	1.15	1.39	
c	0.014	0.021	0.36	0.53	
D	0.590	0.610	14.99	15.49	

