




Feature

High Speed Power Switching, Logic level
 Enhanced Body diode dv/dt capability
 Enhanced Avalanche Ruggedness
 100% UIS Tested, 100% Rg Tested
 Lead Free, Halogen Free

Application

Synchronous Rectification in SMPS
 Hard Switching and High Speed Circuit
 DC/DC in Telecoms and Industrial

DFN
3.3*3.3







=25°C (unless otherwise specified)


		=25°C		
		=100°C		
		=25°C		
			±	
		=25°C		
		=25°C		
				°C


				°C/W
				°C/W



A 4x4 grid of 16 empty white squares. A single continuous red line starts at the bottom-left square and extends horizontally across all four columns to the right.







SYMBOL	DIMENSIONAL REQS		
	MIN	NOM	MAX
A	0.70	0.75	0.80
b	0.25	0.30	0.35
c	0.10	0.15	0.25
D	3.25	3.35	3.45
D1	3.00	3.10	3.20
D2	1.78	1.88	1.98
D3	---	0.13	---
E	3.20	3.30	3.40
E1	3.00	3.15	3.20
E2	2.39	2.49	2.59
e	0.65BSC		
H	0.30	0.39	0.50
L	0.30	0.40	0.50
L1	---	0.13	---
θ	---	10°	12°
M	*	*	0.15
<i>* Not specified</i>			